

## Body Leak Tester (BLT)

### Proven Technology - Efficient Results

The BLT is a completely self-contained enclosure on casters and easily moved by a single person.

The unit is designed and built with rugged industrial and automotive grade components for many years of service.

The unit is designed for standard 110 volt power supply and 25' power cord is provided. European and other supply power systems are available.

Our available BLT models can deliver up to 400 CFM (679 M3/HR) into the vehicle at a specific pressure range, measuring inches of water column (wc). Flow accuracy is dependent on application.

A 15' x 6" diameter hose is furnished with quick connect fittings. The vehicle window template or other vehicle interface is by the End User. The DDC controller allows the input of desired pressure (0-1.0" wc). The system operation is automatic. The on board VFD slowly ramps the fan until vehicle pressure reaches the desired set point. Indication lights acknowledge set point achievement or a fault condition for excessive flow.



### Specifications

Model	Features	Voltage Available
BLT 2.0	Standard flow	110/220v/1ph/50/60 Hz
BLT 2.0 PV	Pressure and vacuum test; Standard flow	110/220v/1ph/50/60 Hz
BLT 2.0 HF	High flow	220/380/440v/3ph/50/60 Hz
BLT 2.0 HFPV	Pressure and vacuum test; High Flow	220/380/440v/3ph/50/60 Hz